

Tii-Foam 31



Uses

To produce a light weight density's product

Advantage

- Produces a consistent pre-foam
- Suitable for produce a wide range of finished density
- Reduce cost of product as per density allowed

Description

Tii-Fom 31 is concentrated foaming agent which special formulated from selected surfactant material, so it produces stable foaming in term of distribution and size of foams

This product can be used for cement (mortar) and gypsum to generate foam so as to create light weight cement or gypsum product

By controlled variation of the amount of pre-foamed added to premixed product, the production of a desired density finished product can be achieved

Properties

- Appearance : Colorless to slightly yellow liquid
- Specific gravity : 1.03 g/cm³ at 23 °C
- pH value : 7.5 – 8.5 (10% solution)
- Viscosity : Approx. 100 mPas at 30 °C
- Odor : No strange odor

Handling

Provide proper protection equipment against accidental may occur

Packaging

150 kgs drum

Tii-Foam 31



Shelf life

12 months with stored properly and kept tightly sealed

Storage

It is recommended to be stored at temperature between 25-40 °C. Store in cool and dry place avoid heating and missing the product. Keep container properly close, do not leave container in open case. Provide good ventilation.

PT. TIRTA INTIWARNA INDONESIA

Wisma GKBI Lt. 39, Suite 3901

Jl. Jend. Sudirman No. 28

Jakarta - Indonesia 10210

Telp 021-22122220

Email : info@tirtaintiwarna.com

